


Usos y aplicaciones

Se utilizan como vigas o columnas en diversas aplicaciones estructurales.

Perfil normal U



U.P.N.	Dimensiones					Peso G kg/m	Sección S cm ²	Valores estáticos				
	h mm	b mm	s mm	t mm	Xg cm			Jx cm ⁴	Jy cm ⁴	Wx cm ³	Wy cm ³	ix=ly cm
80	80	45	6,0	8,0	1,45	8,6	11,0	106	19,4	26,5	6,4	3,10
100	100	50	6,0	8,5	1,55	10,6	13,5	206	29,3	41,2	8,5	3,91
120	120	55	7,0	9,0	1,60	13,3	17,0	364	43,2	60,7	11,1	4,62
140	140	60	7,0	10,0	1,75	16,0	20,4	605	62,7	86,4	14,8	5,45
160	160	65	7,5	10,5	1,84	18,8	24,0	925	85,3	115,6	18,3	6,21
180	180	70	8,0	11,0	1,92	21,9	28,0	1350	114,0	150,0	22,4	6,95
200	200	75	8,5	11,5	2,01	25,2	32,2	1910	148,0	191,0	27,0	7,70
220	220	80	9,0	12,5	2,14	29,3	37,4	2690	197,0	244,5	33,6	8,48
240	240	85	9,5	13,0	2,23	33,1	42,3	3600	248,0	300,0	39,6	9,22
260	260	90	10,0	14,0	2,36	37,8	48,3	4820	317,0	370,0	47,7	9,99
280	280	95	10,0	15,0	2,53	41,8	53,3	6280	399,0	448,0	57,2	10,90
300	300	100	10,0	16,0	2,70	46,1	58,8	8030	495,0	535,0	67,8	11,70
320	320	100	14,0	17,5	2,60	59,4	75,8	10870	597,0	679,0	80,6	12,10
350	350	100	14,0	16,0	2,40	60,6	77,3	12840	570,0	733,7	75,0	12,90
380	380	102	13,5	16,0	2,38	63,0	80,4	15760	615,0	829,5	78,7	14,00
400	400	110	14,0	18,0	2,65	71,7	91,5	20350	846,0	1017,5	102,0	14,90
												3,04

Consultar stock y entrega antes de realizar las compras.